

SHELBY SPECIALTY

#4235

January 2002

Specifications:

- Outer Shell:** Domestic 3.25 oz Pigskin. Reverse Grain, Abrasion resistant, multidirectional fiber structure. Hide has a full chrome primary tannage and a special chrome retannage. Additionally, hide has a halogenated organic dispersion flame retardant chemical added at the end of coloring operation
- Thermal Liner:** 10.75 oz. Lin. Yd. Dyester fabric. 1.49 yd/lb, 22 WPI, 31 CPI. Yarn size 35/1, 12.5/1
- Thread:** Sewn with high burst Strength Kevlar (30/5) lock stitch, 8-10 stitches per inch
- Hanger Loop:** ¼” fire retardant, Split Cowhide, Hanger Loop
- Label:** Label shall be Permanently Attached to each glove and certifies the glove meets or exceeds CAL-OSHA requirements. Label shall include: “1981 Meets FED-OSHA 29 CFR, 1910.156-165. Meets CAL-OSHA SPECS, TITLE & ARTICLE 10.1 para. 347. Each glove to be stamped with MFR. Name, size, “Made in USA” and Lot No. All ¼-½” letters in black permanent ink.
- Origin:** Made in U.S.A.

Sizes:

XXS, XS, S, M, L, XL, J

Design & Construction:

Glove shall be a gunn cut pattern with straight thumb. Thermal lining sewn in at fingertips and wrist area. The glove body shall extend 1” above the wrist crease & shall have a shirred elastic snugger at the wrist. Wrist area of glove is of continuous leather eliminating a “V” at outer side of wrist, ensuring a close fit at wrist opening.

*Tanned hide does not contain PCP (Pentachlorophenol). It is salts or esters.