

SHELBY SPECIALTY

#5009

January 2002

Specifications:

Outer Shell:	Heavy weight 2.75-3.25 oz., reverse grain Pigskin (Tanned by Wolverine Leathers)
Leather:	Abrasion Resistant, Multidirectional Fiber Structure Leather Leather Passes FAR 25.8536 Vertical Flame Test
Wrist Pull:	3" x 3 1/2" Round Leather Pull, Sewn to Wristlet & Glove Body
Thread:	Lock Stitch Sewn with high burst strength Kevlar Thread (8 to 10 stitches per inch). Spun Kevlar Thread, Tex 70, 27.5 to 30.0/4 count (conforms to NFPA 1971 and 1975)
Wrist:	Flame retardant 4" Nomex Wristlet
Lining:	Flame retardant treated estrotron lining
Label:	Meets or Exceeds current CAL & Fed-OSHA requirements CE Marked to the PREN 659 (European Standard)
Origin:	Made in U.S.A.

Sizes:

XXS, XS, S, M, L, XL

Design & Constructions

The glove shall be a Gunn cut pattern with wing thumb construction. A completely sewn, one-piece liner is permanently affixed to the glove shell in the fingertips and wrist areas. This prevents any lining pullout and creates a uniform inside lining even after repeated use in fire fighting conditions. The glove extends 2" above the wrist crease and has a shirred elastic snugger at the wrist to create a better fit.