

# SHELBY SPECIALTY GLOVES

## #5281 & 5283

### Specifications:

**Outer Shell:** Heavy Weight, Fire Retardant 3.5 oz. Blue Cowhide Leather

**Thermal Liner:** 7 oz Cotton and Self Extinguishing Fleece (SEF).

**Protective Barrier:** CROSSTECH Glove Insert

**Wristlet:** Nomex 10.5 oz per yard, double ply, 3" Wristlet. Wristlet sewn to liner, and then sewn separately to the glove shell. Not required on #5283.

**Wrist Pull:** 3" x 3 1/2" Round Leather Pull, Sewn to Wristlet & Glove Body.

**Thread:** Sewn with High burst strength Kevlar (30/5) lock stitch, 8-10 stitches per inch.

**Hanger Loop:** 1/4" fire retardant, Cowhide, Hanger Loop

**Label:** Label shall be Permanently Attached to each glove and certifies the glove meets or exceeds the requirements of the latest NFPA standards (1971, Standard on Protective Ensemble for Structural Fire Fighting, (2007 Edition). Label shall be durable and include the following information: name or designation of manufacture; model; name or style number; lot or serial number; size; date of certification tests; patent numbers; cleaning and care instructions. Label to be sewn to inside of glove. Glove is constructed, tested, and labeled in accordance with the NFPA Standard on Protective Ensemble for Structural Fire Fighting, NFPA 1971 – 2007 Edition. The glove is certified by the Safety Equipment Institute (SEI).

**Origin:** Made in U.S.A.

**Sizes:** XXS, XS, S, M, L, XL, J

### Design & Construction:

Glove shell is a gunn cut pattern with wing thumb and wrap around index finger. Lining is completely sewn Cotton/ S.E.F. and Crosstech glove inserts attached at all finger sidewalls for optimal fingertip control and touch. Proven finger sidewall attachment method helps eliminate bulky fingertip excess material and space. Glove body shall extend 2" above wrist crease & shall have shirred elastic snugger at wrist.